



## DIAPER CHANGING STATION – 100SSE

### PART 1 GENERAL

#### 1.1 SECTION INCLUDES

- A. Diaper changing stations.

#### 1.2 SUBMITTALS

- A. Product Data: Manufacturer's data sheets on each product to be used, including:
  - 1. Preparation instructions and recommendations.
  - 2. Storage and handling requirements and recommendations.
  - 3. Installation methods.

#### 1.3 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.

#### 1.4 PROJECT CONDITIONS

- A. Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for optimum results. Do not install products under environmental conditions outside manufacturer's recommended limits.

#### 1.5 WARRANTY

- A. Warranty: Provide manufacture's standard limited 5-year warranty. All warranties are effective from the date of initial shipment from manufacturer.

### PART 2 PRODUCTS

#### 2.1 MANUFACTURERS

- A. Acceptable Manufacturer: Foundations Worldwide, Inc., which is located at: 5216 Portside Dr., Medina, OH 44256 ; Toll Free Tel: 877-716-2757; Tel: 330-722-5033; Fax: 330-722-5037; Email:[request info \(info@foundations.com\)](mailto:info@foundations.com); Web:[www.foundations.com/changing-stations](http://www.foundations.com/changing-stations)
- B. Substitutions: Not permitted.

## 2.2 DIAPER CHANGING STATIONS

- A. Diaper changing stations shall meet ASTM safety standards, include ANSI warning labels, and shall be ADA compliant when installed.
- B. Special Needs Diaper Changing Station:
  - 1. Product: 100-SSE-R - Extended Length Changer (Recessed) as manufactured by Foundations Worldwide, Inc.
    - a. Rough-in dimensions for recessed unit: 63.25 inches W by 21.75 inches H (1607 mm W by 552 mm H).
    - b. Changing surface extends 17.875 inches (454 mm) from wall in open position.
  - 2. Product: 100-SSE-SM - Extended Length Changer (Surface Mounted) as manufactured by Foundations Worldwide, Inc.
    - a. Required mounting surface 14.75 inches (375 mm) high by 48 inches (1219 mm) wide.
    - b. Changing surface extends 21.375 inches (543 mm) from wall in open position.
  - 3. Constructed of heavy-duty type 304 brushed stainless steel and is rated to support a static load of 400 lb (181 kg).
  - 4. Replaceable high-hygiene polystyrene tray.
  - 5. Dual pneumatic gas springs provide easy and safe open/close operation.
  - 6. When closed, unit projects 1 inch (25 mm) from wall if recessed or 4 inches (102 mm) if surface mounted.
  - 7. Replaceable high-hygiene polystyrene tray.
  - 8. Features cushioned safety corners.
  - 9. One-hand operation safety strap.

## PART 3 EXECUTION

### 3.1 EXAMINATION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.

### 3.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

### 3.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions.

### 3.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

END OF SECTION