



DIAPER CHANGING STATION –5240259

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Diaper changing stations.

1.2 SUBMITTALS

- A. Product Data: Manufacturer's data sheets on each product to be used, including:
 - 1. Preparation instructions and recommendations.
 - 2. Storage and handling requirements and recommendations.
 - 3. Installation methods.

1.3 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.

1.4 PROJECT CONDITIONS

- A. Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for optimum results. Do not install products under environmental conditions outside manufacturer's recommended limits.

1.5 WARRANTY

- A. Warranty: Provide manufacture's standard limited 5-year warranty. All warranties are effective from the date of initial shipment from manufacturer.

PART 2 PRODUCTS

2.1 MANUFACTURERS

- A. Acceptable Manufacturer: Foundations Worldwide, Inc., which is located at: 5216 Portside Dr., Medina, OH 44256 ; Toll Free Tel: 877-716-2757; Tel: 330-722-5033; Fax: 330-722-5037; Email:[request info \(info@foundations.com\)](mailto:info@foundations.com); Web:www.foundations.com/changing-stations
- B. Substitutions: Not permitted.

2.2 DIAPER CHANGING STATIONS

- A. Diaper changing stations shall meet ASTM safety standards, include ANSI warning labels, and shall be ADA compliant when installed.
- B. Horizontal Polyethylene with Stainless Steel Frame Diaper Changing Station:
 - 1. Product: 5240259 - Horizontal Polyethylene Diaper Changing Station as manufactured by Foundations Worldwide, Inc.
 - a. Models shall include built-in liner dispensers, diaper hooks, mounting hardware, one-hand operation safety strap and buckle.
 - b. Provide backer plate mounting bracket.
 - c. Recessed, required rough-in opening 35.625 inches (905 mm) wide by 19.625 inches (499 mm) high.
 - d. Changing surface extends 14.25 inches (362 mm) from wall in open position.
 - 2. Replaceable high-hygiene polystyrene tray.
 - 3. Constructed of heavy-duty type 304 brushed stainless steel.
 - 4. Pneumatic gas spring provides easy and safe open/close operation.
 - 5. One-hand operation safety strap.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.

3.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

3.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions.

3.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

END OF SECTION